SCALE: I" = 600'

RECORD OF SURVEY NO. 31-17

BEING A SURVEY OF LOT 3, SECTION 9 T.8 N., R.23 E., M.D.B.& M. MONO COUNTY, CALIFORNIA B.L.M. LEASE #S-4427 "WALKER LANDFILL SITE"

SURVEYORS STATEMENT

THIS MAP CORRECTLY REPRESENTS A SURVEY MADE BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE REQUIREMENTS OF THE LAND SURVEYORS ACT AT THE REQUEST OF MONO COUNTY IN AUGUST, 1985



COUNTY SURVEYORS STATEMENT

THIS MAP HAS BEEN EXAMINED IN ACCORDANCE WITH SECTION 8766 OF THE LAND SURVEYORS ACT THIS ____ DAY OF _____, 1986



COUNTY SURVEYOR R.C.E. 22549

RECORDERS CERTIFICATE

FILED THIS 22 DAY OF JAVINGEY , 1986

AT 2:50 p.m. IN BOOK 2 OF County Suveyor

AT PAGE(S) 12, 12A AT THE REQUEST

OF MONO COUNTY Ro Fee # 4267

RENN NOLAN COUNTY RECORDER

DIA. I.P. AND BRASS CAP IN A

T8N R23E 6

S4 S3

ROCK MOUND:

LEGEND:

- FOUND POINT AS NOTED
- O SET 2" DIA. IRON PIPE AND TAG "L.S. 4686" IN ROCK MOUND, UNLESS OTHERWISE NOTED
- M MEASURED
- P PROPORTIONED FROM RECORD INFORMATION (R)
- R RECORD PER 1941 U.S.G.L.O. DEPENDENT RESURVEY OF T.8 N., R. 23 E., M. D. M., UNDER SPECIAL INSTRUCTIONS DATED JULY 1, 1941

BASIS OF BEARINGS:

THE BASIS OF BEARINGS FOR THIS SURVEY IS N.O° 06' 00" E. FOR THE EAST LINE OF THE SOUTHEAST QUARTER OF SECTION 9 AS PER A U.S.G.L.O. DEPENDENT RESURVEY OF T.8 N., R. 23 E., M.D.M. UNDER SPECIAL INSTRUCTIONS DATED JULY 1, 1941

SURVEYORS NOTE:

WEST 1/4 CORNER, FOUND I" DIA. I.P. AND BRASS CAP

IN A ROCK MOUND: ...

IN ESTABLISHING THE CORNERS FOR GOVERNMENT LOT 3, THE DETERMINATION NOT TO HOLD THE COUNTY MONUMENT AS ESTABLISHED PER CORNER RECORD NO. 8N23-16-1 WAS BASED ON THE FOLLOWING:

I. B.L.M., WHEN CONTACTED, DID NOT WISH TO RECOGNIZE THE EVIDENCE PROVIDED ON THE ABOVE REFERENCED CORNER RECORD.

2. LOT 3 WAS NOT CREATED UNTIL THE OFFICIAL GOVERNMENT

PLAT WAS ACCEPTED ON OCT. 5, 1945

3. IT WAS DETERMINED THAT THE CORNERS FOR LOT 3 SHOULD THEN BE ESTABLISHED BASED ON THE MONUMENTS SET BY WILSON & JOHNSON AS INDICATED ON THE 1945 GOVT. PLAT

NORTH 1/4 CORNER, FOUND I" DIA. I.P. AND BRASS CAP IN A ROCK MOUND: .. N.E. SECTION COR., FOUND 2" N.89°57'44"W. 2841.38' (M) N.89°45'W. 42.82 Ch. (R)

FOUND U.S.G.L.O. PIPE AND CAP AT S.W. CORNER SEC. 9 PER 1945 U.S. GOVT. PLAT S.89°50'47"W. 2715.50'(P) 24.42' (M) 24.48' RECORD PER MONO CO. CORNER RECORD No.8N23-16-1 FOUND S.W. SECTION COR. AS ESTABLISHED PER MONO COUNTY CORNER RECORD 8N23-16-1 ON FILE IN THE MONO COUNTY PUBLIC WORKS DEPT.. CORNER IS A 2" DIA. I.P. AND BRASS CAP IN A MONUMENT WELL:

2690.20'(M) 40.82Ch.(R) 2731.34 N.0° 05' 31"E. N.0° 06'E. .50 5402. S8 | S9 S17 | S16 1975 URVEY EAST 1/4 CORNER, FOUND I" DIA. I.P. AND BRASS CAP IN A ROCK MOUND: 2775.33 2679.90 CENTER SEC. SEE PAGE 2 5455.23 N. 89° 12′ 14″ E. BEARING 2696.82' 40.82Ch. (+ N. 1º 18' 02" W. N.0°06'00"E. N.0°06'E. 4 2671.16' Ö "BASIS SOUTH 1/4 CORNER, ESTABLISHED BY SINGLE PROPORTION -NOT SET 120.01['] (P) 1.82 Ch. (R) SEE DETAIL "B" 2715.50'(P) 41.18 Ch. (R) S. 89°44' 13"W. 2589.75' (M) S.89°50'47"W. 2835.51 (M) S.89°59'W. 39.36Ch.(R)

N.0°32'15" W. 2640.63 N.0°14'E. 40.04Ch. (SEE DETAIL "A" **ABOVE** s.89° 59′ W. 43.00 Ch.(R) S.W. SECTION COR., FOUND FOUND 2" DIA. I.P. AND "MONO COUNTY SURVEYOR" TAG IN ROCK MOUND AT WITNESS 2" DIA. I.P. AND BRASS CAP: 88 S9 CORNER FOR SOUTH 1/4 CORNER AS SET PER S17 S16 MONO COUNTY CORNER RECORD 8N23-9-1

. S.E. SECTION COR., FOUND 2" DIA. I.P. AND BRASS CAP IN A **ROCK MOUND:**

SIO S16 S15

..south ¼ corner S.26°05'06"E. 8.64'(M)-· S. 89°44'13"W. 2589.75'(M) S. 89° 50' 47" W. S.89°50'47"W. 2715.50' (P) N.86° 01' 20" E. 116.49' (M) WITNESS CORNER FOUND 3/4" I.P. AND TIN LEANING WSTLY.

ON FILE IN THE MONO CO. PUBLIC WORKS DEPT. : '40